

PAT-NO: JP02010129766A
DOCUMENT-IDENTIFIER: JP 2010129766 A
TITLE: PLASMA PROCESSING APPARATUS
PUBN-DATE: June 10, 2010

INVENTOR-INFORMATION:

NAME	COUNTRY
TANDO, TAKUMI	N/A
YOKOGAWA, KATANOBU	N/A
IZAWA, MASARU	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
HITACHI HIGH-TECHNOLOGIES CORP	N/A

APPL-NO: JP2008302628
APPL-DATE: November 27, 2008

INT-CL-ISSUED:

TYPE	IPC	DATE	IPC-OLD
IPCP	H01L21/3065	20060101	H01L021/3065
IPFC	H01L21/205	20060101	H01L021/205
IPFC	H01L21/265	20060101	H01L021/265
IPFC	H01L21/683	20060101	H01L021/683

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a means for controlling the temperature of a semiconductor wafer at high speed and uniformly in a plane in large heat input etching processing.

SOLUTION: A plasma processing apparatus plasmizes a processing gas and subjects a sample W to be processed mounted on a sample table to surface treatment using the plasma. The plasma processing apparatus has a refrigerant flow passage 2 formed in the sample table and constituting an evaporator of a cooling cycle, and uniformly controls the in-plane temperature of the sample to be processed by controlling the enthalpy of the refrigerant supplied to the refrigerant flow passage 2 and thereby keeping the flow mode in the refrigerant flow passage 2, namely in the sample table, in the state of a gas-liquid two-phase state. If by any chance dry out of the refrigerant occurs in the refrigerant flow passage 2 because the heat input etc., of plasma increases, it is possible to increase speed of a compressor 7 and inhibit the dry out from occurring in the refrigerant flow passage 2. Further, if the refrigerant supplied to the refrigerant flow passage 2 is liquefied, the refrigerant supplied into the refrigerant flow passage 2 is kept in the gas-liquid two-phase state by controlling a flow rate valve 16 for heat exchange water and a temperature control water tank 17.

COPYRIGHT: (C) 2010, JPO&INPIT